

Salvage Packaging allows for the transport of damaged, defective, or leaking packaging. The large salvage packaging unit can hold one of our RIKUTEC IBC. A container is also available to hold our RIKUTEC drum. This specific salvage packaging is manufactured in Germany and UN approved according to ADR/RID/IMDG codes, packaging groups II and III.

ADR 2015 makes special provisions for transport packaging used to carry dangerous goods when the original packaging has leaked, is damaged or defective or if it does not conform to ADR requirements. Any packaging with a volume of more than 60 liters that is involved in a spill must be transported in salvage packaging.

Product characteristics

- → Construction made of 3 mm steel sheet
- → Reinforced edging
- → Full length fork sleeves
- → Sturdy stacking corners with crane eyes
- → Suitable for pick-up by pallet jack or forklift
- → Lid fasteners, one lockable
- → Lid with special seal
- → Finish: hot-dip galvanized

UN-APPROVALS

- (u) 50AT/Y/D/BAM 14727-BAUER/4960/
- (u) 50AT/Y/D/BAM 14809-BAUER/6010/
- (u) 50AT/Y/D/BAM 14808-BAUER/6010/
- (u) 50AT/Y/D/BAM 14807-BAUER/6010/

Volume (liters)	Ext. Dimensions (mm) l x w x h	Internal Dimensions (mm) l x w x h	Can be stacked	Total permitted weight (Kg)	Container weight (Kg)
2135	1565 x1365 x1560	1400 x1200 x1250	2 high	2486	424